

SPECIFICATION

Electronic Version 1.2.8

Stylesheet Version 1.0

[METHOD FOR DETERMINING RESTORED POSITION]

Background of Invention

[0001] Field of the Invention

[0002] The invention relates in general to a method for determining restored position, and more particular, to a restoration method to avoid missing line and image repetition.

[0003] Related Art of the Invention

[0004] Due to advancing and fast-developing electronic techniques, the electronic industry has become one of the most important industries in modern society. Many high performance calculating systems are consequently being produced, and more and more electronic products are being used in daily life. In recent years, the growing processing speed and data storage capacity of the processor has greatly enhanced the performance of image processing, while the image processor such as the optical scanner or digital camera have become widely applied.

[0005] In the current operating process of the scanner, the graphic data generating speed is far faster than the data transmission speed between the scanner and the host, and therefore the graphic data scanned by the scanner requires a place for temporary storage. Such place for temporary storage is called a buffer, which ranges between about 32 Kbytes to about 512 Kbytes.

[0006] The faster the graphic data is generated; the more graphic data is stored in the buffer. When the buffer is full of the graphic data, the scanner has to stop scanning. If the scan continues under such circumstances, the graphic data will be lost, or operation problems may occur.

[0009] The smearing procedure is normally determined by the low transmission speed of interface connected to the host, such as the SCSI, USB and EPP. Alternatively, it also occurs when the computer host is too busy with other operation processes to read data from the interface. As a result, the graphic data is accumulated in the buffer until it is completely filled to cause smearing.

Summary of Invention

[0012] The method for determining the restored position provided by the present invention includes the following steps. In the first step, a scanner head moves along a first direction to scan a document. In the second step, the scanner head stops moving, and the position where the scanner head stops is defined as a restored position. Meanwhile, the data of the document located at the restored position is scanned by the scanner head, while the scanned data is defined as the restored graphic data. In the third step, the scanner head moves to a second direction opposing to the first

direction with a first distance. In the fourth step, the scanner head moves along the first direction with a second distance to reach an initial scanning position, where the second distance is smaller than the first distance. In the fifth step, after moving along the second direction with the second distance, the scanner head proceeds in a stepping manner to scan a plurality of corresponding graphic data. In the sixth step, being compared to the restored graphic data, the scanned graphic data closest is selected and defined as the connecting graphic data. In the seventh step, the graphic data subsequent to the connecting graphic data is connected to the restored data.

[0013] According to one embodiment of the present invention, an additional step for erasing the scanned graphic data prior to the connecting graphic data is required, while the connecting graphic data can be used to replace the restored graphic data. In addition, while performing the third step, the first distance includes 36 steps. That is, the scanner head moves 36 steps along the second direction. While performing the fourth step, the scanner head moves 34 steps along the first direction.

[0014] In one embodiment of the present invention, the restored graphic data comprises a plurality of standard pixels, and each scanned graphic data comprises a plurality of pixels. While performing the sixth step, a part of the standard pixels is used as the comparison reference to compare with a part of the pixels of each graphic data in the corresponding positions. Alternatively, while performing the sixth step, all the standard pixels can be used as the comparison reference to compare to the pixels of each of the graphic data in the corresponding position.

[0015] Accordingly, the present invention compares the scanned graphic data with the restored graphic data to select the graphic data closest to the restored graphic data. The selected graphic data scanned subsequently can thus be connected with the restored graphic data correctly.

Brief Description of Drawings

[0016] These, as well as other features of the present invention, will become more apparent upon reference to the drawings wherein:

[0017] Figure 1 and 2 are process flows showing the method for determining restored

position according to the present invention;

[0018] Figure 3 is a schematic drawing showing the arrangement of the standard pixels of the restored graphic data in one embodiment of the present invention; and

[0019] Figure 4 is a schematic drawing showing the arrangement of the pixels of the graphic data.

Detailed Description

[0020] Referring to Figures 1 and 2, flow charts of a method to determine restored position in one preferred embodiment of the present invention are shown. In Figure 1, when the scanner (not shown) is scanning, the scanner head moves along a first direction 180, where the movement of the scanner head is in a stepping manner. The scanned graphic data is then stored in the buffer (not shown) of the scanner. When the buffer has insufficient capacity, the scanner head stops moving. The position where the scanner head stops is defined as the restored position 110. The data of the document scanned by the scanner head at the restored position 110 is defined as the restored graphic data.

[0021] The scanner head then moves with a first distance along a second direction to reach an initial position 130. For example, in a stepping manner, the scanner head moves 36 steps to reach the initial position 130. The second direction 190 is an opposite direction to the first direction 180 in this embodiment.

[0022] Referring to Figure 2, after the scanner head reaches the initial position 130, the scanner head moves along the first direction 180 with a second distance 140 to reach an initial scanning position 150. The second distance 140 is smaller than the first distance 120. The scanner head obtains a graphic data by scanning at the initial scanning position 150, and such graphic data is defined as the initial graphic data. It is appreciated that before reaching the initial scanning position 150, sufficient capacity of the buffer of the scanner is required to store the subsequent scanned graphic data. For the relationship between the remaining capacity of the buffer and the movement of the scanner head refer to the Taiwanese Patent No. 432861; whereby the scanning speed can be increased.

[0023] After the scanner head moves with the second distance 140 along the first direction 180, the scanner head continues moving along the first direction 180 and scans the document 110 until the buffer is again short of capacity. The scanner head proceeds in a stepping manner. A graphic data is scanned for each step that the scanner head steps forward. In one embodiment, the scanner head steps many steps to various positions such as the first to eighth positions 152, 154, 156, 158, 160, 162, 164 and 166. Corresponding to the first to eighth positions 152 to 166, first to eighth graphic data are scanned, respectively.

[0024] After the scanner head starts scanning, a comparison step is performed. That is, the scanned graphic data such as the first to the eighth graphic data are compared to the restored graphic data, respectively, among which the one closest to the restored graphic data, for example, the second graphic data, is selected as the connecting graphic data.

[0025] After realizing that the second graphic data is the one closest to the restored graphic data, the third graphic data is connected to the restored graphic data. The initial graphic data, the first graphic data and the second graphic data are removed. Therefore, the subsequently scanned graphic data can be correctly connected to the previously scanned graphic data without the problems of missing line and image repetition. Alternatively, the restored graphic data can also be replaced by the second graphic data.

[0026] Referring to Figures 3 and 4, Figure 3 schematically shows arrangement of the standard pixels of the restored graphic data, and Figure 4 schematically shows arrangement of the pixels of the scanned graphic data. As shown in Figure 3, the restored graphic data 200 comprises a plurality of standard pixels 202, while in Figure 4, each of the scanned graphic data 300 comprises a plurality of pixels 302. During the comparison procedure, a part of the standard pixels 202 can be used as the comparison reference to respectively compare a part of the pixels 302 for each of the graphic data 300. The part of the pixels to be compared includes parts of the pixels of the initial graphic data, the first to the fourth graphic data, while the pixels 302 to be compared to the standards pixels 202 are in the positions corresponding to those of the standard pixels 302, respectively. For example, the one hundredth to two

hundredth pixels 302 are compared to the one hundredth to the two hundredth standard pixels 202. Alternatively, all of the standard pixels 202 can also be used as the comparison reference to respectively compare each of the pixels 302 of each graphic data. Again, the pixels 302 are compared to the standard pixels 202 in the corresponding positions.

[0027] According to the above, the present invention selects a closest graphic data of a restored graphic data by comparing the scanned graphic data with the restored graphic data, such that the subsequently scanned graphic data can be correctly connected to avoid the missing line and data repetition.

[0028] Other embodiments of the invention will appear to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. It is intended that the specification and examples are to be considered as exemplary only, with a true scope and spirit of the invention being indicated by the following claims.